




---

 PRODUCT-DETAILS

## AF09-30-10-11

### AF09-30-10-11 24-60V50/60HZ 20-60VDC Contactor




---

#### General Information

<b>Extended Product Type:</b>	AF09-30-10-11
<b>Product ID:</b>	1SBL137001R1110
<b>EAN:</b>	3471523110014
<b>Catalog Description:</b>	AF09-30-10-11 24-60V50/60HZ 20-60VDC Contactor
<b>Long Description:</b>	The AF09-30-10-11 is a 3 pole - 690 V IEC or 600 UL contactor with 1 built-in auxiliary contact and screw terminals, controlling motors up to 4 kW / 400 V AC (AC-3) or 5 hp / 480 V UL and switching power circuits up to 25 A (AC-1) or 25 A UL general use. Thanks to the AF technology, the contactor has a wide control voltage range (24-60 V 50/60 Hz and 20-60 V DC), managing large control voltage variations, reducing panel energy consumptions and ensuring distinct operations in unstable networks. Furthermore, surge protection is built-in, offering a compact solution. AF contactors have a block type design, can be easily extended with add-on auxiliary contact blocks and an additional wide range of accessories.
<b>Display Name:</b>	AF09-30-10-11

---

#### Ordering

<b>Minimum Order Quantity:</b>	1 piece
--------------------------------	---------

Customs Tariff Number: 85364900

## Popular Downloads

EPLAN Data:	9AAC159656_EPLAN
Data Sheet, Technical Information:	1SBC100214C0202
Instructions and Manuals:	1SBC101027M6801
Instructions and Manuals (Part 2):	1SAC200017M0002
CAD Dimensional Drawing:	2CDC001079B0201

## Dimensions

Product Net Width:	45 mm
Product Net Depth / Length:	77 mm
Product Net Height:	86 mm
Product Net Weight:	0.27 kg

## Technical

Number of Main Contacts NO:	3
Number of Main Contacts NC:	0
Number of Auxiliary Contacts NO:	1
Number of Auxiliary Contacts NC:	0
Number of Poles:	3P
Standards:	IEC/EN 60947-1, IEC/EN 60947-4-1, UL 60335-2-40 LZGH2 A2L, UL 60947-4-1, CSA C22.2 No. 60335-2-40 LZGH2 A2L, CSA C22.2 No. 60947-4-1
Rated Operational Voltage:	Auxiliary Circuit 690 V Main Circuit 690 V
Rated Frequency (f):	Auxiliary Circuit 50 / 60 Hz Control Circuit 50 / 60 Hz Main Circuit 50 / 60 Hz
Conventional Free-air Thermal Current (I <sub>th</sub> ):	acc. to IEC 60947-4-1, Open Contactors $\Theta = 40\text{ °C}$ 35 A acc. to IEC 60947-5-1, $\Theta = 40\text{ °C}$ 16 A
Rated Operational Current AC-1 (I <sub>e</sub> ):	(690 V) 40 °C 25 A (690 V) 60 °C 25 A (690 V) 70 °C 22 A
Rated Operational Current AC-3 (I <sub>e</sub> ):	(415 V) 60 °C 9 A (440 V) 60 °C 9 A (500 V) 60 °C 9.5 A (690 V) 60 °C 7 A (380 / 400 V) 60 °C 9 A (220 / 230 / 240 V) 60 °C 9 A
Rated Operational Current AC-3e (I <sub>e</sub> ):	(415 V) 60 °C 9 A (440 V) 60 °C 9 A (500 V) 60 °C 9.5 A (690 V) 60 °C 7 A (380 / 400 V) 60 °C 9 A (220 / 230 / 240 V) 60 °C 9 A

**Rated Operational Current AC-15 (I<sub>e</sub>):** (500 V) 2 A  
 (690 V) 2 A  
 (24 / 127 V) 6 A  
 (220 / 240 V) 4 A  
 (400 / 440 V) 3 A

---

**Rated Operational Current DC-1 (I<sub>e</sub>):** (110 V) 1-Pole, 40 °C 10 A  
 (110 V) 1-Pole, 60 °C 10 A  
 (110 V) 1-Pole, 70 °C 10 A  
 (110 V) 2 Poles in Series, 40 °C 25 A  
 (110 V) 2 Poles in Series, 60 °C 25 A  
 (110 V) 2 Poles in Series, 70 °C 22 A  
 (110 V) 3 Poles in Series, 40 °C 25 A  
 (110 V) 3 Poles in Series, 60 °C 25 A  
 (110 V) 3 Poles in Series, 70 °C 22 A  
 (220 V) 2 Poles in Series, 40 °C 10 A  
 (220 V) 2 Poles in Series, 60 °C 10 A  
 (220 V) 2 Poles in Series, 70 °C 10 A  
 (220 V) 3 Poles in Series, 40 °C 25 A  
 (220 V) 3 Poles in Series, 60 °C 25 A  
 (220 V) 3 Poles in Series, 70 °C 22 A  
 (72 V) 1-Pole, 40 °C 25 A  
 (72 V) 1-Pole, 60 °C 25 A  
 (72 V) 1-Pole, 70 °C 22 A  
 (72 V) 2 Poles in Series, 40 °C 25 A  
 (72 V) 2 Poles in Series, 60 °C 25 A  
 (72 V) 2 Poles in Series, 70 °C 22 A  
 (72 V) 3 Poles in Series, 40 °C 25 A  
 (72 V) 3 Poles in Series, 60 °C 25 A  
 (72 V) 3 Poles in Series, 70 °C 22 A

---

**Rated Operational Current DC-3 (I<sub>e</sub>):** (110 V) 1-Pole, 40 °C 6 A  
 (110 V) 1-Pole, 60 °C 6 A  
 (110 V) 1-Pole, 70 °C 6 A  
 (110 V) 2 Poles in Series, 40 °C 25 A  
 (110 V) 2 Poles in Series, 60 °C 25 A  
 (110 V) 2 Poles in Series, 70 °C 22 A  
 (110 V) 3 Poles in Series, 40 °C 25 A  
 (110 V) 3 Poles in Series, 60 °C 25 A  
 (110 V) 3 Poles in Series, 70 °C 22 A  
 (220 V) 2 Poles in Series, 40 °C 6 A  
 (220 V) 2 Poles in Series, 60 °C 6 A  
 (220 V) 2 Poles in Series, 70 °C 6 A  
 (220 V) 3 Poles in Series, 40 °C 25 A  
 (220 V) 3 Poles in Series, 60 °C 25 A  
 (220 V) 3 Poles in Series, 70 °C 22 A  
 (72 V) 1-Pole, 40 °C 25 A  
 (72 V) 1-Pole, 60 °C 25 A  
 (72 V) 1-Pole, 70 °C 22 A  
 (72 V) 2 Poles in Series, 40 °C 25 A  
 (72 V) 2 Poles in Series, 60 °C 25 A  
 (72 V) 2 Poles in Series, 70 °C 22 A  
 (72 V) 3 Poles in Series, 40 °C 25 A  
 (72 V) 3 Poles in Series, 60 °C 25 A  
 (72 V) 3 Poles in Series, 70 °C 22 A

---

<b>Rated Operational Current DC-5 (I<sub>e</sub>):</b>	(110 V) 1-Pole, 40 °C 4 A (110 V) 1-Pole, 60 °C 4 A (110 V) 1-Pole, 70 °C 4 A (110 V) 2 Poles in Series, 40 °C 10 A (110 V) 2 Poles in Series, 60 °C 10 A (110 V) 2 Poles in Series, 70 °C 10 A (110 V) 3 Poles in Series, 40 °C 25 A (110 V) 3 Poles in Series, 60 °C 25 A (110 V) 3 Poles in Series, 70 °C 22 A (220 V) 2 Poles in Series, 40 °C 4 A (220 V) 2 Poles in Series, 60 °C 4 A (220 V) 2 Poles in Series, 70 °C 4 A (220 V) 3 Poles in Series, 40 °C 9 A (220 V) 3 Poles in Series, 60 °C 9 A (220 V) 3 Poles in Series, 70 °C 9 A (72 V) 1-Pole, 40 °C 9 A (72 V) 1-Pole, 60 °C 9 A (72 V) 1-Pole, 70 °C 9 A (72 V) 2 Poles in Series, 40 °C 25 A (72 V) 2 Poles in Series, 60 °C 25 A (72 V) 2 Poles in Series, 70 °C 22 A (72 V) 3 Poles in Series, 40 °C 25 A (72 V) 3 Poles in Series, 60 °C 25 A (72 V) 3 Poles in Series, 70 °C 22 A
<b>Rated Operational Current DC-13 (I<sub>e</sub>):</b>	(24 V) 6 A / 144 W (48 V) 2.8 A / 134 W (72 V) 1 A / 72 W (110 V) 0.55 A / 60 W (125 V) 0.55 A / 69 W (220 V) 0.27 A / 60 W (250 V) 0.27 A / 68 W (400 V) 0.15 A / 60 W (500 V) 0.13 A / 65 W (600 V) 0.1 A / 60 W
<b>Rated Operational Power AC-3 (P<sub>e</sub>):</b>	(400 V) 4 kW (415 V) 4 kW (440 V) 4 kW (500 V) 5.5 kW (690 V) 5.5 kW (380 / 400 V) 4 kW (220 / 230 / 240 V) 2.2 kW
<b>Rated Operational Power AC-3e (P<sub>e</sub>):</b>	(415 V) 4 kW (440 V) 4 kW (500 V) 5.5 kW (690 V) 5.5 kW (380 / 400 V) 4 kW (220 / 230 / 240 V) 2.2 kW
<b>Rated Short-time Withstand Current Low Voltage (I<sub>cw</sub>):</b>	at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 150 A at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 35 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 60 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 300 A at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 80 A for 0.1 s 140 A for 1 s 100 A
<b>Maximum Breaking Capacity:</b>	cos phi=0.45 (cos phi=0.35 for I <sub>e</sub> > 100 A) at 440 V 250 A cos phi=0.45 (cos phi=0.35 for I <sub>e</sub> > 100 A) at 690 V 106 A
<b>Rated Insulation Voltage (U<sub>i</sub>):</b>	acc. to IEC 60947-4-1 690 V acc. to IEC 60947-5-1 690 V acc. to UL/CSA 600 V
<b>Rated Impulse Withstand Voltage (U<sub>imp</sub>):</b>	6 kV
<b>Maximum Electrical Switching Frequency:</b>	(AC-1) 600 cycles per hour (AC-15) 1200 cycles per hour (AC-2 / AC-4) 300 cycles per hour (AC-3) 1200 cycles per hour (DC-13) 900 cycles per hour

<b>Maximum Mechanical Switching Frequency:</b>	3600 cycles per hour
<b>Rated Control Circuit Voltage (U<sub>c</sub>):</b>	50 Hz 24 ... 60 V 60 Hz 24 ... 60 V DC Operation 20 ... 60 V
<b>Power Loss:</b>	at 6 A per Pole 0.1 W at Rated Operating Conditions AC-1 per Pole 0.8 W at Rated Operating Conditions AC-3 per Pole 0.1 W
<b>Operate Time:</b>	Between Coil De-energization and NC Contact Closing 13 ... 98 ms Between Coil De-energization and NO Contact Opening 11 ... 95 ms Between Coil Energization and NC Contact Opening 38 ... 90 ms Between Coil Energization and NO Contact Closing 40 ... 95 ms
<b>Mounting on DIN Rail:</b>	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
<b>Mounting by Screws (not supplied) :</b>	2 x M4 Screws Placed Diagonally
<b>Connecting Capacity Main Circuit:</b>	Flexible with Ferrule 1/2x 0.75 ... 6 mm <sup>2</sup> Flexible with Insulated Ferrule 1x 0.75 ... 4 mm <sup>2</sup> Flexible with Insulated Ferrule 2x 0.75 ... 2.5 mm <sup>2</sup> Rigid Solid 1/2x 1 ... 4 mm <sup>2</sup> Rigid Stranded 1/2x 1 ... 6 mm <sup>2</sup>
<b>Connecting Capacity Auxiliary Circuit:</b>	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm <sup>2</sup> Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm <sup>2</sup> Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm <sup>2</sup> Rigid Solid 1/2x 1 ... 2.5 mm <sup>2</sup> Rigid Stranded 1/2x 1 ... 2.5 mm <sup>2</sup>
<b>Connecting Capacity Control Circuit:</b>	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm <sup>2</sup> Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm <sup>2</sup> Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm <sup>2</sup> Rigid Solid 1/2x 1 ... 2.5 mm <sup>2</sup> Rigid Stranded 1/2x 1 ... 2.5 mm <sup>2</sup>
<b>Wire Stripping Length:</b>	Auxiliary Circuit 10 mm Control Circuit 10 mm Main Circuit 10 mm
<b>Degree of Protection:</b>	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
<b>Tightening Torque:</b>	Auxiliary Circuit 1.2 N·m Control Circuit 1.2 N·m Main Circuit 1.5 N·m
<b>Terminal Type:</b>	Screw Terminals
<b>Product Name:</b>	Block Contactor

## Technical UL/CSA

<b>NEMA Size:</b>	00
<b>Continuous Current Rating NEMA:</b>	9 A
<b>Horsepower Rating NEMA:</b>	(115 V AC) Single Phase 1/3 Hp (200 V AC) Three Phase 1-1/2 Hp (230 V AC) Single Phase 1 Hp (230 V AC) Three Phase 1-1/2 Hp (460 V AC) Three Phase 2 Hp (575 V AC) Three Phase 2 Hp
<b>Maximum Operating Voltage UL/CSA:</b>	Main Circuit 600 V
<b>General Use Rating UL/CSA:</b>	(600 V AC) 25 A

<b>Horsepower Rating UL/CSA:</b>	(120 V AC) Single Phase 3/4 hp (200 ... 208 V AC) Three Phase 2 hp (220 ... 240 V AC) Three Phase 2 hp (240 V AC) Single Phase 1-1/2 hp (440 ... 480 V AC) Three Phase 5 hp (550 ... 600 V AC) Three Phase 7-1/2 hp
<b>Connecting Capacity Main Circuit UL/CSA:</b>	Rigid Solid 1/2x 16-10 AWG Rigid Stranded 1/2x 16-10 AWG
<b>Connecting Capacity Auxiliary Circuit UL/CSA:</b>	Rigid Solid 1/2x 18-14 AWG Rigid Stranded 1/2x 18-14 AWG
<b>Connecting Capacity Control Circuit UL/CSA:</b>	Rigid Solid 1/2x 18-14 AWG Rigid Stranded 1/2x 18-14 AWG
<b>Tightening Torque UL/CSA:</b>	Auxiliary Circuit 11 in-lb Control Circuit 11 in-lb Main Circuit 13 in-lb
<b>Full Load Amps Motor Use:</b>	(120 V AC) Single Phase 13.8 A (200 ... 208 V AC) Three Phase 7.8 A (220 ... 240 V AC) Three Phase 6.8 A (240 V AC) Single Phase 10 A (440 ... 480 V AC) Three Phase 7.6 A (550 ... 600 V AC) Three Phase 9 A

## Environmental

<b>Ambient Air Temperature:</b>	Close to Contactor Fitted with Thermal O/L Relay -25 ... 60 °C Close to Contactor without Thermal O/L Relay -40 ... 70 °C Close to Contactor for Storage -60 ... +80 °C
<b>Climatic Withstand:</b>	Category B according to IEC 60947-1 Annex Q
<b>Maximum Operating Altitude Permissible:</b>	Without Derating 3000 m
<b>Resistance to Shock acc. to IEC 60068-2-27:</b>	Closed, Shock Direction: B1 25 g Open, Shock Direction: B1 5 g Shock Direction: A 30 g Shock Direction: B2 15 g Shock Direction: C1 25 g Shock Direction: C2 25 g
<b>Resistance to Vibrations:</b>	4g Closed Position & 2g Open position 5 ... 300 Hz
<b>Pollution Degree:</b>	3

## Material Compliance

<b>Conflict Minerals Reporting Template (CMRT):</b>	9AKK108467A5658
<b>REACH Declaration:</b>	2CMT2021-006202
<b>RoHS Declaration:</b>	2CMT2021-006277
<b>RoHS Information:</b>	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
<b>SCIP:</b>	fd4714ff-9365-48a3-94a4-2bebf1f23 China

<b>Simplified SCIP:</b>	8297a722-cc0f-4782-a8f8-075acea41bd6 Spain 60c3dbdc-391e-4daf-9a85-70e3bd0d2ea0 Croatia 0bb95f7e-5bd1-4d7f-b192-2477a25d35da Czechia 0b055dbd-1066-4155-a4d4-3771b2c41d57 France 2f7a69c0-b1af-42e2-8d87-80f8ee6b4b25 Germany b217d838-e5ce-4026-978c-a13ceee6013 Germany 1f0a558a-9d04-4edd-b827-65ac41a26dcc Sweden 2045ed6b-b82b-4628-90cd-d4e7f27bb979 Germany 880d376c-4f31-4f54-b579-aab4c5291566 Poland 75051088-0f2d-4586-871a-6331dd71d145 France d551d6e5-5f59-4717-867a-b2bc44c17f6b Sweden ac2002f8-634f-49f3-9820-e719cf270af6 Denmark 5abac707-494a-4531-b610-fb9643ebba41 Germany 736597e3-e353-4116-b956-c6c7b4698b4b Bulgaria 5b8d698d-7c0a-4e4b-8e45-4e67bb7a8c3a Estonia bdb7092f-5d60-4ec6-9da8-e559b8617f36 Finland 31c30f9a-d89e-4369-8c43-e3d693e857ec Hungary 81bc28c3-da00-43f3-88e4-8d2dbf3fdc09 Hungary 91d5fca5-b899-468c-a97a-4cdf403f4a58 Norway 20d8f677-c436-4f8f-8fdc-90f414d5bf1f Netherlands c6fee10d-6aa1-4cd6-8dc6-e09fec5969dd Belgium b2f25054-3b81-43fb-b349-fb478b0c00c1 Greece 35fb5949-f388-41ae-9d4f-b963db63e20a Portugal b433b770-8005-4c63-9194-9e95ab1d890a Poland 2e4f67af-ba3e-4f23-8231-a16fc7eaf9aa Germany fc32984e-d501-4530-a019-c70a65038877 Poland 52949e89-943e-45a7-83b4-a076ae89ea4c Belgium
<b>Toxic Substances Control Act - TSCA:</b>	2CMT2023-006525
<b>WEEE B2C / B2B:</b>	Business To Business
<b>WEEE Category:</b>	5. Small Equipment (No External Dimension More Than 50 cm)

### ABB EcoSolutions

<b>ABB EcoSolutions:</b>	Yes
<b>ABB Site Meeting Group Waste To Landfill Target:</b>	No non-hazardous waste is sent to a landfill
<b>EcoSolutions Profile:</b>	1SBC100156C0308
<b>End Of Life Disassembling Instructions:</b>	1SBC101080M6801
<b>Environmental Product Declaration - EPD:</b>	1SBD250584E3000
<b>Improved Energy Efficiency for Customers:</b>	Product Efficiency - Product considered more energy-efficient compared to similar product on market or older products from the same line
<b>Recyclability Rate of the Product acc. to EN45555:</b>	Design for Closing Resource Loops - Standard EN45555 - 92.7 %

### Certificates and Declarations

<b>A2L Certificate – UL:</b>	9AKK108469A4875 9AKK108469A4879
<b>ABS Certificate:</b>	ABS_20-2060694-PDA
<b>BV Certificate:</b>	BV_2634H24898C1
<b>CB Certificate:</b>	CB_SE-117714
<b>CCC Certificate:</b>	CCC_2024010304656669
<b>CQC Certificate:</b>	CQC2010010304445624 CQC2020010304298240

<b>Declaration of Conformity - CCC:</b>	2020980304001253 2020980304001082
<b>Declaration of Conformity - CE:</b>	1SBD250000U1000
<b>Declaration of Conformity - UKCA:</b>	1SBD250031U1000
<b>DNV Certificate:</b>	DNV_TAE00001AF-4
<b>KC Certificate:</b>	KC_HW02016-15004C
<b>LR Certificate:</b>	LRS_LR23403517TA-02
<b>RINA Certificate:</b>	RINA_ELE142224XG
<b>RMRS Certificate:</b>	RMRS_1802705280
<b>UL Certificate:</b>	UL-US-2150887-5 UL-CA-2142658-5
<b>UL Listing Card:</b>	E312527

## Container Information

<b>Package Level 1 Units:</b>	box 1 piece
<b>Package Level 1 Width:</b>	87 mm
<b>Package Level 1 Depth / Length:</b>	79 mm
<b>Package Level 1 Height:</b>	47 mm
<b>Package Level 1 Gross Weight:</b>	0.27 kg
<b>Package Level 1 EAN:</b>	3471523110014

## External Classifications and Standards

<b>Object Classification Code:</b>	Q
<b>ETIM 7:</b>	EC000066 - Power contactor, AC switching
<b>ETIM 8:</b>	EC000066 - Power contactor, AC switching
<b>ETIM 9:</b>	EC000066 - Power contactor, AC switching
<b>eClass:</b>	V11.0 : 27371003
<b>UNSPSC:</b>	39121529
<b>IDEA Granular Category Code (IGCC):</b>	4758 >> lec Contactors
<b>E-Number (Finland):</b>	3705800
<b>E-Number (Sweden):</b>	3210016

## Accessories

Identifier	Description	Type	Qty	Unit Of Measure
1SBN010015R1001	CE5-01D0.1 Auxiliary Contact Block	CE5-01D0.1	1	piece
1SBN010015R1010	CE5-10D0.1 Auxiliary Contact Block	CE5-10D0.1	1	piece
1SBN010016R1001	CE5-01W0.1 Auxiliary Contact Block	CE5-01W0.1	1	piece
1SBN010016R1010	CE5-10W0.1 Auxiliary Contact Block	CE5-10W0.1	1	piece
1SBN010017R1001	CE5-01D2 Auxiliary Contact Block	CE5-01D2	1	piece

Identifier	Description	Type	Qty	Unit Of Measure
1SBN010017R1010	CE5-10D2 Auxiliary Contact Block	CE5-10D2	1	piece
1SBN010018R1001	CE5-01W2 Auxiliary Contact Block	CE5-01W2	1	piece
1SBN010018R1010	CE5-10W2 Auxiliary Contact Block	CE5-10W2	1	piece
1SBN010013R1010	CB5-10 Impulse Contact Block	CB5-10	1	piece
1SBN010013R1001	CB5-01 Impulse Contact Block	CB5-01	1	piece
1SBN010110R1010	CA4-10 Auxiliary Contact Block	CA4-10	1	piece
1SBN010110T1010	CA4-10-T Auxiliary Contact Block	CA4-10-T	1	piece
1SBN010110R1001	CA4-01 Auxiliary Contact Block	CA4-01	1	piece
1SBN010110T1001	CA4-01-T Auxiliary Contact Block	CA4-01-T	1	piece
1SBN010111R1010	CC4-10 Leading Auxiliary Contact Block	CC4-10	1	piece
1SBN010111R1001	CC4-01 Lagging Auxiliary Contact Block	CC4-01	1	piece
1SBN010120R1011	CAL4-11 Auxiliary Contact Block	CAL4-11	1	piece
1SBN010120T1011	CAL4-11-T Auxiliary Contact Block	CAL4-11-T	1	piece
1SBN010140R1022	CA4-22E Auxiliary Contact Block	CA4-22E	1	piece
1SBN010140R1031	CA4-31E Auxiliary Contact Block	CA4-31E	1	piece
1SBN010140R1040	CA4-40E Auxiliary Contact Block	CA4-40E	1	piece
1SBN010140R1004	CA4-04E Auxiliary Contact Block	CA4-04E	1	piece
1SBN010140R1322	CA4-22U Auxiliary Contact Block	CA4-22U	1	piece
1SBN010140R1122	CA4-22M Auxiliary Contact Block	CA4-22M	1	piece
1SBN010151R1011	CAT4-11E Auxiliary Contact / Coil Terminal Block	CAT4-11E	1	piece
1SBN010140R1331	CA4-31U Auxiliary Contact Block	CA4-31U	1	piece
1SBN010140R1131	CA4-31M Auxiliary Contact Block	CA4-31M	1	piece
1SBN010151R1111	CAT4-11M Auxiliary Contact / Coil Terminal Block	CAT4-11M	1	piece
1SBN010140R1340	CA4-40U Auxiliary Contact Block	CA4-40U	1	piece
1SBN010140R1113	CA4-13M Auxiliary Contact Block	CA4-13M	1	piece
1SBN010151R1311	CAT4-11U Auxiliary Contact / Coil Terminal Block	CAT4-11U	1	piece
1SBN070156T1000	LDC4 Additional Coil Terminal Block	LDC4	1	piece
1SBN030105T1000	VM4 Mechanical Interlock Unit	VM4	1	piece
1SBN081306T1000	BEA16-4 Connecting Link with Manual Motor Starter	BEA16-4	1	piece
1SBN010140R1104	CA4-04M Auxiliary Contact Block	CA4-04M	1	piece
1SBN030111R1000	VEM4 Mechanical and Electrical Interlock Set	VEM4	1	piece
1SBN020112R1000	TEF4-ON Frontal Electronic Timer	TEF4-ON	1	piece
1SBN020113R1000	TEF4S-ON Frontal Electronic Timer	TEF4S-ON	1	piece
1SBN010134R1011	CAL4-11K Auxiliary Contact Block	CAL4-11K	1	piece
1SBN020114R1000	TEF4-OFF Frontal Electronic Timer	TEF4-OFF	1	piece
1SBN081311R1000	BER16-4 Connection Set for Reversing Contactors	BER16-4	1	piece
1SBN020115R1000	TEF4S-OFF Frontal Electronic Timer	TEF4S-OFF	1	piece
1SBN081313R2000	BEY16-4 Connection Set for Star-Delta Starter	BEY16-4	1	piece
1SBN071303T1000	LY16-4 Connecting Strip	LY16-4	1	piece
1SBN071305R1000	LF16-4 Connecting Strip	LF16-4	1	piece
1SBN110108T1000	BX4 Protective Cover	BX4	1	piece

Identifier	Description	Type	Qty	Unit Of Measure
1SBN072304R1000	LH38-4 Connecting Strip	LH38-4	1	piece
1SBN071306R1000	LG16-4 Connecting Strip	LG16-4	1	piece
1SBN040100R1011	WA4-11 24-60V50/60HZ-DC Mechanical Latching Unit	WA4-11	1	piece
1SBN040100R1014	WA4-14 250-500V50/60HZ-DC Mechanical Latching Unit	WA4-14	1	piece
1SBN110122T1000	BDT4 Test Block	BDT4	1	piece
1SBN040100R1010	WA4-10 24VDC Mechanical Latching Unit	WA4-10	1	piece
1SBN040100R1012	WA4-12 48-130V50/60HZ-DC Mechanical Latching Unit	WA4-12	1	piece
1SBN060100R1000	RA4 Interface Relay	RA4	1	piece
1SBN010146R1104	CA4-04MK Auxiliary Contact Block	CA4-04MK	1	piece
1SBN040100R1013	WA4-13 100-250V50/60HZ-DC Mechanical Latching Unit	WA4-13	1	piece
1SBN081322R1000	BER16-4KF Connection Set for Reversing Contactors	BER16-4KF	1	piece
1SBN010146R1113	CA4-13MK Auxiliary Contact Block	CA4-13MK	1	piece
1SBN081323R2000	BEY16-4KF Connection Set for Star-Delta Starter	BEY16-4KF	1	piece
1SBN070159T1000	LDC4K Additional Coil Terminal Block	LDC4K	1	piece
1SBN010160R1001	CA4-01K Auxiliary Contact Block	CA4-01K	1	piece
1SBN010146R1022	CA4-22EK Auxiliary Contact Block	CA4-22EK	1	piece
1SBN081314R1000	BEP16-30 Phase to phase connection	BEP16-30	1	piece
1SBN010160R1010	CA4-10K Auxiliary Contact Block	CA4-10K	1	piece
1SBN010146R1122	CA4-22MK Auxiliary Contact Block	CA4-22MK	1	piece
1SBN010160T1001	CA4-01K-T Auxiliary Contact Block	CA4-01K-T	1	piece
1SBN010160T1010	CA4-10K-T Auxiliary Contact Block	CA4-10K-T	1	piece
1SBN030113R1000	VEM4K Mechanical and Electrical Interlock Set	VEM4K	1	piece
1SBN010146R1031	CA4-31EK Auxiliary Contact Block	CA4-31EK	1	piece
1SBN010146R1131	CA4-31MK Auxiliary Contact Block	CA4-31MK	1	piece
1SBN010146R1040	CA4-40EK Auxiliary Contact Block	CA4-40EK	1	piece

## Categories

Products > Low Voltage Products and Systems > Control Products > Contactors > Block Contactors > AF Contactors > AF09

