



 PRODUCT-DETAILS

AF26-40-00-13

AF26-40-00-13 100-250V50/60HZ-DC Contactor



General Information

Extended Product Type:	AF26-40-00-13
Product ID:	1SBL237201R1300
EAN:	3471523115231
Catalog Description:	AF26-40-00-13 100-250V50/60HZ-DC Contactor
Long Description:	The AF26-40-00-13 is a 4 pole - 690 V IEC or 600 UL contactor with screw terminals, controlling motors up to 11 kW / 400 V AC (AC-3) and switching power circuits up to 45 A (AC-1) or 45 A UL general use. Thanks to the AF technology, the contactor has a wide control voltage range (100-250 V 50/60 Hz and DC), managing large control voltage variations, reducing panel energy consumptions and ensuring distinct operations in unstable networks. Furthermore, surge protection is built-in, offering a compact solution. AF contactors have a block type design, can be easily extended with add-on auxiliary contact blocks and an additional wide range of accessories.
Display Name:	AF26-40-00-13

Ordering

Minimum Order Quantity:	1 piece
Customs Tariff Number:	85364900

Popular Downloads

EPLAN Data:	9AAC159659_EPLAN
Data Sheet, Technical Information:	1SBC100214C0202
Instructions and Manuals:	1SBC101027M6801
Instructions and Manuals (Part 2):	1SAC200017M0002
CAD Dimensional Drawing:	2CDC001079B0201

Dimensions

Product Net Width:	45 mm
Product Net Depth / Length:	101 mm
Product Net Height:	86 mm
Product Net Weight:	0.36 kg

Technical

Number of Main Contacts NO:	4
Number of Main Contacts NC:	0
Number of Auxiliary Contacts NO:	0
Number of Auxiliary Contacts NC:	0
Number of Poles:	4P
Standards:	IEC/EN 60947-1, IEC/EN 60947-4-1, UL 60335-2-40 LZGH2 A2L, UL 60947-1, UL 60947-4-1, CSA C22.2 No. 60335-2-40 LZGH2 A2L, CAN/CSA C22.2 No.60947-1, CAN/CSA C22.2 No.60947-4-1
Rated Operational Voltage:	Main Circuit 690 V
Rated Frequency (f):	Control Circuit 50 / 60 Hz Main Circuit 50 / 60 Hz
Conventional Free-air Thermal Current (I_{th}):	acc. to IEC 60947-4-1, Open Contactors $\Theta = 40\text{ °C}$ 55 A
Rated Operational Current AC-1 (I_e):	(690 V) 40 °C 45 A (690 V) 60 °C 40 A (690 V) 70 °C 32 A
Rated Operational Current AC-3 (I_e):	(415 V) 60 °C 21.2 A (440 V) 60 °C 20 A (500 V) 60 °C 17.6 A (690 V) 60 °C 10.5 A (380 / 400 V) 60 °C 22 A (220 / 230 / 240 V) 60 °C 23.2 A

Rated Operational Current DC-1 (I_e):	(110 V) 2 Poles in Series, 40 °C 45 A (110 V) 2 Poles in Series, 60 °C 40 A (110 V) 2 Poles in Series, 70 °C 32 A (110 V) 3 Poles in Series, 40 °C 45 A (110 V) 3 Poles in Series, 60 °C 40 A (110 V) 3 Poles in Series, 70 °C 32 A (110 V) 4 Poles in Series, 40 °C 45 A (110 V) 4 Poles in Series, 60 °C 40 A (110 V) 4 Poles in Series, 70 °C 32 A (220 V) 3 Poles in Series, 40 °C 45 A (220 V) 3 Poles in Series, 60 °C 40 A (220 V) 3 Poles in Series, 70 °C 32 A (220 V) 4 Poles in Series, 40 °C 45 A (220 V) 4 Poles in Series, 60 °C 40 A (220 V) 4 Poles in Series, 70 °C 32 A (72 V) 1-Pole, 40 °C 45 A (72 V) 1-Pole, 60 °C 40 A (72 V) 1-Pole, 70 °C 32 A (72 V) 2 Poles in Series, 40 °C 45 A (72 V) 2 Poles in Series, 60 °C 40 A (72 V) 2 Poles in Series, 70 °C 32 A (72 V) 3 Poles in Series, 40 °C 45 A (72 V) 3 Poles in Series, 60 °C 40 A (72 V) 3 Poles in Series, 70 °C 32 A (72 V) 4 Poles in Series, 40 °C 45 A (72 V) 4 Poles in Series, 60 °C 40 A (72 V) 4 Poles in Series, 70 °C 32 A
Rated Operational Power AC-3 (P_e):	(400 V) 11 kW (415 V) 11 kW (440 V) 11 kW (500 V) 11 kW (690 V) 9 kW (220 / 230 / 240 V) 5.5 kW
Rated Short-time Withstand Current Low Voltage (I_{cw}):	at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 300 A at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 55 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 150 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 450 A at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 225 A
Rated Insulation Voltage (U_i):	acc. to IEC 60947-4-1 690 V acc. to UL/CSA 600 V
Rated Impulse Withstand Voltage (U_{imp}):	6 kV
Maximum Electrical Switching Frequency:	(AC-1) 600 cycles per hour
Maximum Mechanical Switching Frequency:	3600 cycles per hour
Rated Control Circuit Voltage (U_c):	50 Hz 100 ... 250 V 60 Hz 100 ... 250 V DC Operation 100 ... 250 V
Power Loss:	at Rated Operating Conditions AC-1 per Pole 1.6 W at Rated Operating Conditions AC-3 per Pole 0.42 W
Operate Time:	Between Coil De-energization and NC Contact Closing 13 ... 98 ms Between Coil De-energization and NO Contact Opening 11 ... 95 ms Between Coil Energization and NC Contact Opening 38 ... 90 ms Between Coil Energization and NO Contact Closing 40 ... 95 ms
Mounting on DIN Rail:	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Mounting by Screws (not supplied) :	2 x M4 Screws Placed Diagonally
Connecting Capacity Main Circuit:	Flexible with Ferrule 1/2x 1.5 ... 16 mm ² Flexible with Insulated Ferrule 1/2x 1.5 ... 16 mm ² Rigid Solid 1/2x 1.5 ... 4 mm ² Rigid Stranded 1/2x 1.5 ... 16 mm ²

Connecting Capacity Control Circuit:	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ² Rigid Solid 1/2x 1 ... 2.5 mm ² Rigid Stranded 1/2x 1 ... 2.5 mm ²
Wire Stripping Length:	Control Circuit 10 mm Main Circuit 12 mm
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
Tightening Torque:	Control Circuit 1.2 N·m Main Circuit 2.5 N·m
Terminal Type:	Screw Terminals
Product Name:	Block Contactor

Technical UL/CSA

Maximum Operating Voltage UL/CSA:	Main Circuit 600 V
General Use Rating UL/CSA:	(600 V AC) 45 A
Connecting Capacity Main Circuit UL/CSA:	Rigid Solid 1/2x 16-10 AWG Rigid Stranded 1/2x 16-6 AWG
Connecting Capacity Control Circuit UL/CSA:	Rigid Solid 1/2x 18-14 AWG Rigid Stranded 1/2x 18-14 AWG
Tightening Torque UL/CSA:	Control Circuit 11 in·lb Main Circuit 22 in·lb

Environmental

Ambient Air Temperature:	Close to Contactor for Storage -60 ... +80 °C Near Contactor for Operation in Free Air -40 ... 70 °C
Climatic Withstand:	Category B according to IEC 60947-1 Annex Q
Maximum Operating Altitude Permissible:	Without Derating 3000 m
Resistance to Shock acc. to IEC 60068-2-27:	Closed, Shock Direction: B1 25 g Open, Shock Direction: B1 5 g Shock Direction: A 30 g Shock Direction: B2 15 g Shock Direction: C1 25 g Shock Direction: C2 25 g
Resistance to Vibrations:	4g Closed Position & 2g Open position 5 ... 300 Hz
Pollution Degree:	3

Material Compliance

Conflict Minerals Reporting Template (CMRT):	9AKK108467A5658
REACH Declaration:	2CMT2021-006202
RoHS Declaration:	2CMT2021-006277
RoHS Information:	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP:	894b9a15-6d1a-4a7a-b1e2-f88ca8aeada0 France

Simplified SCIP:	064d1765-4346-4250-a872-be33228af641 Finland 0f040ca9-f03f-4c5a-a35e-56f279e5e40d Norway 16229975-8743-4fc2-b5f0-a80871880e66 Portugal 2b573fed-f7a0-4e04-9964-f9b3ddfd660e Denmark 396060ec-c30d-4b79-adeb-d2427e23e2b4 Poland 3d72bd32-64aa-4d40-a793-6705ff620f0f Hungary 3e6acbff-7d1b-4f16-be78-64e8ab78fd89 Greece 3eac4d6d-bfd4-4c41-85b9-4a286f67f48d Croatia 40f8c5ca-cd7f-4793-8da2-6a5f6f6b66a6 France 47811304-6522-494f-8cdc-5f2e1b7e0128 Sweden 4e3023d5-bed9-4693-bc33-9e65dc7fdbe5 Poland 6192283f-cfbc-4d8f-abd0-e9ee0998e207 Bulgaria 63c6371b-248b-4b39-981d-d4c4e1d801ea Spain 648436d1-7bf5-4740-acf1-1fbdad4c6be2 Italy 80cccc34-f18b-439c-b21d-54d92b7d425d Hungary 8e25a9ec-19df-45d7-9e07-5fe3b3323269 Estonia 90c25723-65d6-4a25-a2ae-870681008c3e Germany 91ba99ca-3fd9-4020-8827-4ab346e55de8 Sweden 99a9f902-ab47-452c-8e67-11c88c51c283 Belgium a9a4a28f-2ba7-4da1-a9fd-7d71b9467c6b Germany bf04af50-eab9-47cf-b0b2-14cbaf957ea3 Germany c61f4049-4672-4303-8841-e78946cc1dcc Czechia e20cb3e3-e4e9-4d62-8711-f7f8d7b9989d Germany ec5f1824-097b-4644-8561-74999b600345 Netherlands ec6c5997-4553-4d75-8f8f-27de51cb07f9 Belgium f95629c4-c211-403e-90fb-b0fbb1eb8d6d Poland fa26a288-7e06-4da2-a9c6-5ea2f89a644b Germany
-------------------------	--

Toxic Substances Control Act - TSCA:	2CMT2023-006525
WEEE B2C / B2B:	Business To Business
WEEE Category:	5. Small Equipment (No External Dimension More Than 50 cm)

ABB EcoSolutions

ABB EcoSolutions:	Yes
ABB Site Meeting Group Waste To Landfill Target:	No non-hazardous waste is sent to a landfill
EcoSolutions Profile:	1SBC100156C0308
End Of Life Disassembling Instructions:	1SBC101080M6801
Environmental Product Declaration - EPD:	1SBD250584E4000
Improved Energy Efficiency for Customers:	Product Efficiency - Product considered more energy-efficient compared to similar product on market or older products from the same line
Recyclability Rate of the Product acc. to EN45555:	Design for Closing Resource Loops - Standard EN45555 - 94.3 %

Certificates and Declarations

A2L Certificate – UL:	9AKK108469A4875 9AKK108469A4879
ABS Certificate:	ABS_20-2060694-PDA
BV Certificate:	BV_2634H24898C1
CB Certificate:	9AKK108472A2647
CCC Certificate:	CCC_2024010304656668
CQC Certificate:	CQC2010010304445623 CQC2020010304294316

Declaration of Conformity - CCC:	2020980304001254 2020980304001052
Declaration of Conformity - CE:	1SBD250001U1000
Declaration of Conformity - UKCA:	1SBD250032U1000
DNV Certificate:	DNV_TAE00001AF-4
KC Certificate:	KC_HW02016-15002C
LR Certificate:	LRS_LR23403517TA-02
RINA Certificate:	RINA_ELE142224XG
RMRS Certificate:	RMRS_1802705280
UL Certificate:	UL-US-L319322-13-72119002-5 UL-CA-L319322-43-72119002-6
UL Listing Card:	UL_E319322

Container Information

Package Level 1 Units:	box 1 piece
Package Level 1 Width:	87 mm
Package Level 1 Depth / Length:	103 mm
Package Level 1 Height:	47 mm
Package Level 1 Gross Weight:	0.36 kg
Package Level 1 EAN:	3471523115231

External Classifications and Standards

Object Classification Code:	Q
ETIM 7:	EC000066 - Power contactor, AC switching
ETIM 8:	EC000066 - Power contactor, AC switching
ETIM 9:	EC000066 - Power contactor, AC switching
eClass:	V11.0 : 27371003
UNSPSC:	39121529
IDEA Granular Category Code (IGCC):	4758 >> lec Contactors
E-Number (Finland):	3705830
E-Number (Sweden):	3211511

Accessories

Identifier	Description	Type	Qty	Unit Of Measure
1SBN112303T1000	BP38-4 Mounting Piece	BP38-4	1	piece
1SBN113403T1000	BP65-4 Mounting Piece	BP65-4	1	piece
1SBN113903T1000	BP96-4 Mounting Piece	BP96-4	1	piece
1SBN110108T1000	BX4 Protective Cover	BX4	1	piece
1SBN110109W1000	BX4-CA Protective Cover	BX4-CA	1	piece

Identifier	Description	Type	Qty	Unit Of Measure
1SBN010110R1001	CA4-01 Auxiliary Contact Block	CA4-01	1	piece
1SBN010160R1001	CA4-01K Auxiliary Contact Block	CA4-01K	1	piece
1SBN010110T1001	CA4-01-T Auxiliary Contact Block	CA4-01-T	1	piece
1SBN010140R1004	CA4-04E Auxiliary Contact Block	CA4-04E	1	piece
1SBN010110R1010	CA4-10 Auxiliary Contact Block	CA4-10	1	piece
1SBN010160R1010	CA4-10K Auxiliary Contact Block	CA4-10K	1	piece
1SBN010110T1010	CA4-10-T Auxiliary Contact Block	CA4-10-T	1	piece
1SBN010140R1022	CA4-22E Auxiliary Contact Block	CA4-22E	1	piece
1SBN010146R1022	CA4-22EK Auxiliary Contact Block	CA4-22EK	1	piece
1SBN010140R1031	CA4-31E Auxiliary Contact Block	CA4-31E	1	piece
1SBN010146R1031	CA4-31EK Auxiliary Contact Block	CA4-31EK	1	piece
1SBN010140R1040	CA4-40E Auxiliary Contact Block	CA4-40E	1	piece
1SBN010146R1040	CA4-40EK Auxiliary Contact Block	CA4-40EK	1	piece
1SBN010120R1011	CAL4-11 Auxiliary Contact Block	CAL4-11	1	piece
1SBN010134R1011	CAL4-11K Auxiliary Contact Block	CAL4-11K	1	piece
1SBN010120T1011	CAL4-11-T Auxiliary Contact Block	CAL4-11-T	1	piece
1SBN010151R1011	CAT4-11E Auxiliary Contact / Coil Terminal Block	CAT4-11E	1	piece
1SBN010111R1001	CC4-01 Lagging Auxiliary Contact Block	CC4-01	1	piece
1SBN010111R1010	CC4-10 Leading Auxiliary Contact Block	CC4-10	1	piece
1SBN010015R1001	CE5-01D0.1 Auxiliary Contact Block	CE5-01D0.1	1	piece
1SBN010017R1001	CE5-01D2 Auxiliary Contact Block	CE5-01D2	1	piece
1SBN010016R1001	CE5-01W0.1 Auxiliary Contact Block	CE5-01W0.1	1	piece
1SBN010018R1001	CE5-01W2 Auxiliary Contact Block	CE5-01W2	1	piece
1SBN010015R1010	CE5-10D0.1 Auxiliary Contact Block	CE5-10D0.1	1	piece
1SBN010017R1010	CE5-10D2 Auxiliary Contact Block	CE5-10D2	1	piece
1SBN010016R1010	CE5-10W0.1 Auxiliary Contact Block	CE5-10W0.1	1	piece
1SBN010018R1010	CE5-10W2 Auxiliary Contact Block	CE5-10W2	1	piece
1SBN073452R2000	LK96-4F Terminals for Control Lead Connections	LK96-4F	1	piece
1SBN070156T1000	LDC4 Additional Coil Terminal Block	LDC4	1	piece
1SBN070159T1000	LDC4K Additional Coil Terminal Block	LDC4K	1	piece
1SBN071305R1000	LF16-4 Connecting Strip	LF16-4	1	piece
1SBN071306R1000	LG16-4 Connecting Strip	LG16-4	1	piece
1SBN123402R1000	LT52-40 Terminal Shroud	LT52-40	1	piece
1SBN123902R1000	LT80-40 Terminal Shroud	LT80-40	1	piece
1SBN071303T1000	LY16-4 Connecting Strip	LY16-4	1	piece
1SBN060100R1000	RA4 Interface Relay	RA4	1	piece
1SBN020114R1000	TEF4-OFF Frontal Electronic Timer	TEF4-OFF	1	piece
1SBN020112R1000	TEF4-ON Frontal Electronic Timer	TEF4-ON	1	piece
1SBN020115R1000	TEF4S-OFF Frontal Electronic Timer	TEF4S-OFF	1	piece
1SBN020113R1000	TEF4S-ON Frontal Electronic Timer	TEF4S-ON	1	piece
1SBN040100R1010	WA4-10 24VDC Mechanical Latching Unit	WA4-10	1	piece

Identifier	Description	Type	Qty	Unit Of Measure
1SBN040100R1011	WA4-11 24-60V50/60HZ-DC Mechanical Latching Unit	WA4-11	1	piece
1SBN040100R1012	WA4-12 48-130V50/60HZ-DC Mechanical Latching Unit	WA4-12	1	piece
1SBN040100R1013	WA4-13 100-250V50/60HZ-DC Mechanical Latching Unit	WA4-13	1	piece
1SBN040100R1014	WA4-14 250-500V50/60HZ-DC Mechanical Latching Unit	WA4-14	1	piece
1SBN040200R1011	WA4-96-11 24-60V50/60HZ-DC Mechanical Latching Unit	WA4-96-11	1	piece
1SBN040200R1012	WA4-96-12 48-130V50/60HZ-DC Mechanical Latching Unit	WA4-96-12	1	piece
1SBN040200R1013	WA4-96-13 100-250V50/60HZ-DC Mechanical Latching Unit	WA4-96-13	1	piece
1SBN040200R1014	WA4-96-14 250-500V50/60HZ-DC Mechanical Latching Unit	WA4-96-14	1	piece

Categories

Products > Low Voltage Products and Systems > Control Products > Contactors > Block Contactors > AF Contactors > AF26

