



 PRODUCT-DETAILS

AF52-30-11-13

AF52-30-11-13 100-250V50/60HZ-DC Contactor



General Information

Extended Product Type:	AF52-30-11-13
Product ID:	1SBL367001R1311
EAN:	3471523132436
Catalog Description:	AF52-30-11-13 100-250V50/60HZ-DC Contactor
Long Description:	The AF52-30-11-13 is a 3 pole - 690 V IEC or 600 UL contactor with pre-mounted auxiliary contacts and screw terminals, controlling motors up to 22 kW / 400 V AC (AC-3) or 40 hp / 480 V UL and switching power circuits up to 100 A (AC-1) or 80 A UL general use. Thanks to the AF technology, the contactor has a wide control voltage range (100-250 V 50/60 Hz and DC), managing large control voltage variations, reducing panel energy consumptions and ensuring distinct operations in unstable networks. Furthermore, surge protection is built-in, offering a compact solution. AF contactors have a block type design, can be easily extended with add-on auxiliary contact blocks and an additional wide range of accessories.
Display Name:	AF52-30-11-13

Ordering

Minimum Order Quantity:	1 piece
--------------------------------	---------

Customs Tariff Number: 85364900

Popular Downloads

EPLAN Data:	9AAC175973_EPLAN
Data Sheet, Technical Information:	1SBC100214C0202
Instructions and Manuals:	1SBC101036M6801
Instructions and Manuals (Part 2):	1SAC200017M0002
CAD Dimensional Drawing:	2CDC001079B0201

Dimensions

Product Net Width:	67 mm
Product Net Depth / Length:	111 mm
Product Net Height:	125,5 mm
Product Net Weight:	0.99 kg

Technical

Number of Main Contacts NO:	3
Number of Main Contacts NC:	0
Number of Auxiliary Contacts NO:	1
Number of Auxiliary Contacts NC:	1
Number of Poles:	3P
Standards:	IEC/EN 60947-1, IEC/EN 60947-4-1, UL 60335-2-40 LZGH2 A2L, UL 60947-1, UL 60947-4-1, CSA C22.2 No. 60335-2-40 LZGH2 A2L, CSA C22.2 No. 60947-1:22, CSA C22.2 No. 60947-4-1:22
Rated Operational Voltage:	Auxiliary Circuit 690 V Main Circuit 690 V
Rated Frequency (f):	Auxiliary Circuit 50 / 60 Hz Control Circuit 50 / 60 Hz Main Circuit 50 / 60 Hz
Conventional Free-air Thermal Current (I _{th}):	acc. to IEC 60947-4-1, Open Contactors $\Theta = 40\text{ °C}$ 105 A acc. to IEC 60947-5-1, $\Theta = 40\text{ °C}$ 16 A
Rated Operational Current AC-1 (I _e):	(690 V) 40 °C 100 A (690 V) 60 °C 80 A (690 V) 70 °C 70 A
Rated Operational Current AC-3 (I _e):	(415 V) 60 °C 53 A (440 V) 60 °C 53 A (500 V) 60 °C 45 A (690 V) 60 °C 35 A (380 / 400 V) 60 °C 53 A (220 / 230 / 240 V) 60 °C 53 A
Rated Operational Current AC-3e (I _e):	(415 V) 60 °C 53 A (440 V) 60 °C 53 A (500 V) 60 °C 45 A (690 V) 60 °C 35 A (380 / 400 V) 60 °C 53 A (220 / 230 / 240 V) 60 °C 53 A

Rated Operational Current AC-15 (I_e):	(500 V) 2 A (690 V) 2 A (24 / 127 V) 6 A (220 / 240 V) 4 A (400 / 440 V) 3 A
<hr/>	
Rated Operational Current DC-1 (I_e):	(110 V) 2 Poles in Series, 40 °C 100 A (110 V) 2 Poles in Series, 60 °C 80 A (110 V) 2 Poles in Series, 70 °C 70 A (110 V) 3 Poles in Series, 40 °C 100 A (110 V) 3 Poles in Series, 60 °C 80 A (110 V) 3 Poles in Series, 70 °C 70 A (220 V) 3 Poles in Series, 40 °C 100 A (220 V) 3 Poles in Series, 60 °C 80 A (220 V) 3 Poles in Series, 70 °C 70 A (72 V) 1-Pole, 40 °C 100 A (72 V) 1-Pole, 60 °C 80 A (72 V) 1-Pole, 70 °C 70 A (72 V) 2 Poles in Series, 40 °C 100 A (72 V) 2 Poles in Series, 60 °C 80 A (72 V) 2 Poles in Series, 70 °C 70 A (72 V) 3 Poles in Series, 40 °C 100 A (72 V) 3 Poles in Series, 60 °C 80 A (72 V) 3 Poles in Series, 70 °C 70 A
<hr/>	
Rated Operational Current DC-3 (I_e):	(110 V) 2 Poles in Series, 40 °C 100 A (110 V) 2 Poles in Series, 60 °C 80 A (110 V) 2 Poles in Series, 70 °C 70 A (110 V) 3 Poles in Series, 40 °C 100 A (110 V) 3 Poles in Series, 60 °C 80 A (110 V) 3 Poles in Series, 70 °C 70 A (220 V) 3 Poles in Series, 40 °C 100 A (220 V) 3 Poles in Series, 60 °C 80 A (220 V) 3 Poles in Series, 70 °C 70 A (72 V) 1-Pole, 40 °C 100 A (72 V) 1-Pole, 60 °C 80 A (72 V) 1-Pole, 70 °C 70 A (72 V) 2 Poles in Series, 40 °C 100 A (72 V) 2 Poles in Series, 60 °C 80 A (72 V) 2 Poles in Series, 70 °C 70 A (72 V) 3 Poles in Series, 40 °C 100 A (72 V) 3 Poles in Series, 60 °C 80 A (72 V) 3 Poles in Series, 70 °C 70 A
<hr/>	
Rated Operational Current DC-5 (I_e):	(110 V) 2 Poles in Series, 40 °C 100 A (110 V) 2 Poles in Series, 60 °C 80 A (110 V) 2 Poles in Series, 70 °C 70 A (110 V) 3 Poles in Series, 40 °C 100 A (110 V) 3 Poles in Series, 60 °C 80 A (110 V) 3 Poles in Series, 70 °C 70 A (220 V) 3 Poles in Series, 40 °C 100 A (220 V) 3 Poles in Series, 60 °C 80 A (220 V) 3 Poles in Series, 70 °C 70 A (72 V) 1-Pole, 40 °C 100 A (72 V) 1-Pole, 60 °C 80 A (72 V) 1-Pole, 70 °C 70 A (72 V) 2 Poles in Series, 40 °C 100 A (72 V) 2 Poles in Series, 60 °C 80 A (72 V) 2 Poles in Series, 70 °C 70 A (72 V) 3 Poles in Series, 40 °C 100 A (72 V) 3 Poles in Series, 60 °C 80 A (72 V) 3 Poles in Series, 70 °C 70 A
<hr/>	
Rated Operational Current DC-13 (I_e):	(24 V) 6 A / 144 W (48 V) 2.8 A / 134 W (72 V) 1 A / 72 W (110 V) 0.55 A / 60 W (125 V) 0.55 A / 69 W (220 V) 0.27 A / 60 W (250 V) 0.27 A / 68 W (400 V) 0.15 A / 60 W (500 V) 0.13 A / 65 W (600 V) 0.1 A / 60 W

Rated Operational Power AC-3 (P_e):	(400 V) 22 kW (415 V) 30 kW (440 V) 30 kW (500 V) 30 kW (690 V) 30 kW (380 / 400 V) 22 kW (220 / 230 / 240 V) 15 kW
Rated Operational Power AC-3e (P_e):	(415 V) 30 kW (440 V) 30 kW (500 V) 30 kW (690 V) 30 kW (380 / 400 V) 22 kW (220 / 230 / 240 V) 15 kW
Rated Short-time Withstand Current Low Voltage (I_{cw}):	at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 600 A at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 110 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 250 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 1000 A at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 350 A for 0.1 s 140 A for 1 s 100 A
Maximum Breaking Capacity:	cos phi=0.45 (cos phi=0.35 for $I_e > 100$ A) at 440 V 950 A cos phi=0.45 (cos phi=0.35 for $I_e > 100$ A) at 690 V 600 A
Rated Insulation Voltage (U_i):	acc. to IEC 60947-4-1 690 V acc. to IEC 60947-5-1 690 V acc. to UL/CSA 600 V
Rated Impulse Withstand Voltage (U_{imp}):	6 kV
Maximum Electrical Switching Frequency:	(AC-1) 600 cycles per hour (AC-15) 1200 cycles per hour (AC-2 / AC-4) 150 cycles per hour (AC-3) 1200 cycles per hour (DC-13) 900 cycles per hour
Maximum Mechanical Switching Frequency:	3600 cycles per hour
Rated Control Circuit Voltage (U_c):	50 Hz 100 ... 250 V 60 Hz 100 ... 250 V DC Operation 100 ... 250 V
Coil Consumption:	Average Holding Value 50 / 60 Hz 4 V·A Average Holding Value 50 Hz 4 V·A Average Holding Value 60 Hz 4 V·A Average Holding Value DC 2 W Average Holding Value, from Warm State 2 W
Power Loss:	at 6 A per Pole 0.1 W at Rated Operating Conditions AC-1 per Pole 6.3 W at Rated Operating Conditions AC-3 per Pole 1.7 W
Operate Time:	Between Coil De-energization and NC Contact Closing 19 ... 105 ms Between Coil De-energization and NO Contact Opening 17 ... 100 ms Between Coil Energization and NC Contact Opening 38 ... 95 ms Between Coil Energization and NO Contact Closing 42 ... 100 ms
Mounting on DIN Rail:	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Mounting by Screws (not supplied) :	2 x M4 or 2 x M6 Screws Placed Diagonally
Connecting Capacity Main Circuit:	Flexible with Ferrule 1/2x 4 ... 35 mm ² Flexible with Insulated Ferrule 1/2x 4 ... 35 mm ² Rigid Stranded 1/2x 6 ... 35 mm ²
Connecting Capacity Auxiliary Circuit:	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Rigid 1/2x 1 ... 2.5 mm ²

Connecting Capacity Control Circuit:	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ² Rigid Solid 1/2x 1 ... 2.5 mm ² Rigid Stranded 1/2x 1 ... 2.5 mm ²
Wire Stripping Length:	Auxiliary Circuit 10 mm Control Circuit 10 mm Main Circuit 16 mm
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP10
Recommended Screw Driver:	Pozidriv PZ
Tightening Torque:	Auxiliary Circuit 1.2 N-m Control Circuit 1.2 N-m Main Circuit 4 N-m
Terminal Type:	Screw Terminals
Product Name:	Block Contactor

Technical UL/CSA

Maximum Operating Voltage UL/CSA:	Main Circuit 600 V
General Use Rating UL/CSA:	(600 V AC) 80 A
Horsepower Rating UL/CSA:	(120 V AC) Single Phase 3 hp (200 ... 208 V AC) Three Phase 15 hp (220 ... 240 V AC) Three Phase 20 hp (240 V AC) Single Phase 10 hp (440 ... 480 V AC) Three Phase 40 hp (550 ... 600 V AC) Three Phase 50 hp
Connecting Capacity Main Circuit UL/CSA:	Rigid Stranded 1/2x 10-2 AWG
Connecting Capacity Control Circuit UL/CSA:	Rigid Solid 1/2x 18-14 AWG Rigid Stranded 1/2x 18-14 AWG
Tightening Torque UL/CSA:	Auxiliary Circuit 11 in-lb Control Circuit 11 in-lb Main Circuit 35 in-lb
Full Load Amps Motor Use:	(120 V AC) Single Phase 34 A (200 ... 208 V AC) Three Phase 48.3 A (220 ... 240 V AC) Three Phase 54 A (240 V AC) Single Phase 50 A (440 ... 480 V AC) Three Phase 52 A (550 ... 600 V AC) Three Phase 52 A

Environmental

Ambient Air Temperature:	Close to Contactor Fitted with Thermal O/L Relay -40 ... 70 °C Close to Contactor without Thermal O/L Relay -40 ... 70 °C Close to Contactor for Storage -60 ... +80 °C
Climatic Withstand:	Category B according to IEC 60947-1 Annex Q
Maximum Operating Altitude Permissible:	Without Derating 3000 m
Resistance to Shock acc. to IEC 60068-2-27:	Closed, Shock Direction: A 25 g Closed, Shock Direction: B1 25 g Closed, Shock Direction: B2 15 g Closed, Shock Direction: C1 25 g Closed, Shock Direction: C2 25 g Open, Shock Direction: B1 5 g

Resistance to Vibrations:	3g Closed Position & 3g Open Position 5 ... 300 Hz
Pollution Degree:	3

Material Compliance

Conflict Minerals Reporting Template (CMRT):	9AKK108467A5658
REACH Declaration:	2CMT2021-006202
RoHS Declaration:	2CMT2021-006277
RoHS Information:	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP:	eefefca6-2a4a-40be-ba9c-cfffc2d94819 France
Simplified SCIP:	6209b522-07dd-4a67-80ba-9cd50675052f Germany 79470f4e-1c95-40fc-8280-37caf48c17b9 Germany 910957cf-a3ba-44b0-9335-dc577dae72e9 Sweden 357b6148-e7ff-4786-9d91-86399d3b8085 Poland 132b0740-d24e-435a-8f49-3ddfd38ece90 France 2fa8bf47-8d58-4533-8f2a-1e19838b633b Finland 9820ea6d-79bc-460d-9116-c958754cb847 Italy 3f42d8ed-f47b-4791-86c1-3c822bab752d Netherlands 6f1835e4-1588-45bb-a454-fa15faf07d2d Greece e5c52109-3223-42cf-87bf-83beab5a8c24 Germany c8425b50-2d92-49d8-bf65-c94dc83b053a Denmark 596e36f4-4b35-431a-99cb-51ce4fe9891e Germany 8a4185a5-b3a3-4bcb-a43e-7b49966650ec Czechia 9ef837eb-fee1-4ce9-a4da-29e75e2db48e Poland a1cac9d1-df11-4189-8911-ebebc56f9e19 Germany 4cf96436-31a2-4ca3-a1ce-6f52339cf70e Poland a5fecfd8-8045-48c3-b8ef-043d8975e05f Norway 40cf1fde-f811-4ad9-94ab-5f28200c9e81 Spain 19dc6076-72f3-465a-9b00-d2fd321d716d Sweden 4a9b647b-1f2e-4ee8-9863-773f49160cc6 Portugal 9bbefaf1-686d-4902-b91f-4ceb771ae3c2 Hungary e91aea41-c744-498c-8ea4-316945502f99 Belgium 10eabc19-7225-408a-bd4c-512c7d2e8742 Bulgaria
Toxic Substances Control Act - TSCA:	2CMT2023-006525
WEEE B2C / B2B:	Business To Business
WEEE Category:	5. Small Equipment (No External Dimension More Than 50 cm)

ABB EcoSolutions

ABB EcoSolutions:	Yes
ABB Site Meeting Group Waste To Landfill Target:	No non-hazardous waste is sent to a landfill
EcoSolutions Profile:	1SBC100156C0308
End Of Life Disassembling Instructions:	1SBC101081M6801
Environmental Product Declaration - EPD:	1SBD250584E1000
Improved Energy Efficiency for Customers:	Product Efficiency - Product considered more energy-efficient compared to similar product on market or older products from the same line Product Efficiency - Product requires less energy to operate compared to similar product on market or older products from the same line
Recyclability Rate of the Product acc. to EN45555:	Design for Closing Resource Loops - Standard EN45555 - 91.9 %

Certificates and Declarations

A2L Certificate – UL:	9AKK108469A4890 9AKK108469A4892
ABS Certificate:	ABS_20-2060694-PDA
BV Certificate:	BV_2634H36994B2
CB Certificate:	SE-115941
CCC Certificate:	CCC_2024010304648524
Declaration of Conformity - CCC:	2020980304001256 2020980304001074
Declaration of Conformity - CE:	1SBD250000U1000
Declaration of Conformity - UKCA:	1SBD250031U1000
DNV Certificate:	DNV_TAE00001AF-4
KC Certificate:	KC_HW02016-15010C
LR Certificate:	LRS_LR23403517TA-02
RINA Certificate:	RINA_ELE084013XG
RMRS Certificate:	RMRS_1802705280
UL Certificate:	UL-US-L312527-1141-10303102-19 UL-CA-L312527-4141-10303102-19
UL Listing Card:	UL_E312527

Container Information

Package Level 1 Units:	box 1 piece
Package Level 1 Width:	150 mm
Package Level 1 Depth / Length:	150 mm
Package Level 1 Height:	97 mm
Package Level 1 Gross Weight:	1.09 kg
Package Level 1 EAN:	3471523132436

External Classifications and Standards

Object Classification Code:	Q
ETIM 7:	EC000066 - Power contactor, AC switching
ETIM 8:	EC000066 - Power contactor, AC switching
ETIM 9:	EC000066 - Power contactor, AC switching
eClass:	V11.0 : 27371003
UNSPSC:	39121529
IDEA Granular Category Code (IGCC):	4758 >> lec Contactors
E-Number (Finland):	3707023

Accessories

Identifier	Description	Type	Qty	Unit Of Measure
1SBN010015R1001	CE5-01D0.1 Auxiliary Contact Block	CE5-01D0.1	1	piece
1SBN010015R1010	CE5-10D0.1 Auxiliary Contact Block	CE5-10D0.1	1	piece
1SBN010016R1001	CE5-01W0.1 Auxiliary Contact Block	CE5-01W0.1	1	piece
1SBN010016R1010	CE5-10W0.1 Auxiliary Contact Block	CE5-10W0.1	1	piece
1SBN010017R1001	CE5-01D2 Auxiliary Contact Block	CE5-01D2	1	piece
1SBN010017R1010	CE5-10D2 Auxiliary Contact Block	CE5-10D2	1	piece
1SBN010018R1001	CE5-01W2 Auxiliary Contact Block	CE5-01W2	1	piece
1SBN010018R1010	CE5-10W2 Auxiliary Contact Block	CE5-10W2	1	piece
1SBN010013R1010	CB5-10 Impulse Contact Block	CB5-10	1	piece
1SBN010013R1001	CB5-01 Impulse Contact Block	CB5-01	1	piece
1SBN010110R1010	CA4-10 Auxiliary Contact Block	CA4-10	1	piece
1SBN010110T1010	CA4-10-T Auxiliary Contact Block	CA4-10-T	1	piece
1SBN010110R1001	CA4-01 Auxiliary Contact Block	CA4-01	1	piece
1SBN010110T1001	CA4-01-T Auxiliary Contact Block	CA4-01-T	1	piece
1SBN010111R1010	CC4-10 Leading Auxiliary Contact Block	CC4-10	1	piece
1SBN010111R1001	CC4-01 Lagging Auxiliary Contact Block	CC4-01	1	piece
1SBN010120R1011	CAL4-11 Auxiliary Contact Block	CAL4-11	1	piece
1SBN010120T1011	CAL4-11-T Auxiliary Contact Block	CAL4-11-T	1	piece
1SBN010140R1022	CA4-22E Auxiliary Contact Block	CA4-22E	1	piece
1SBN010140R1031	CA4-31E Auxiliary Contact Block	CA4-31E	1	piece
1SBN010140R1040	CA4-40E Auxiliary Contact Block	CA4-40E	1	piece
1SBN010140R1004	CA4-04E Auxiliary Contact Block	CA4-04E	1	piece
1SBN010151R1011	CAT4-11E Auxiliary Contact / Coil Terminal Block	CAT4-11E	1	piece
1SBN070156T1000	LDC4 Additional Coil Terminal Block	LDC4	1	piece
1SBN020112R1000	TEF4-ON Frontal Electronic Timer	TEF4-ON	1	piece
1SBN020113R1000	TEF4S-ON Frontal Electronic Timer	TEF4S-ON	1	piece
1SBN010134R1011	CAL4-11K Auxiliary Contact Block	CAL4-11K	1	piece
1SBN020114R1000	TEF4-OFF Frontal Electronic Timer	TEF4-OFF	1	piece
1SBN020115R1000	TEF4S-OFF Frontal Electronic Timer	TEF4S-OFF	1	piece
1SBN033405T1000	VM96-4 Mechanical Interlock Unit	VM96-4	1	piece
1SBN110108T1000	BX4 Protective Cover	BX4	1	piece
1SBN040100R1011	WA4-11 24-60V50/60HZ-DC Mechanical Latching Unit	WA4-11	1	piece
1SBN083413R2000	BEY65-4 Connection Set for Star-Delta Starter	BEY65-4	1	piece
1SBN040100R1014	WA4-14 250-500V50/60HZ-DC Mechanical Latching Unit	WA4-14	1	piece
1SBN110122T1000	BDT4 Test Block	BDT4	1	piece
1SBN083411R1000	BER65-4 Connection Set for Reversing Contactors	BER65-4	1	piece
1SBN040100R1012	WA4-12 48-130V50/60HZ-DC Mechanical Latching Unit	WA4-12	1	piece
1SBN060100R1000	RA4 Interface Relay	RA4	1	piece
1SBN040100R1013	WA4-13 100-250V50/60HZ-DC Mechanical Latching Unit	WA4-13	1	piece
1SBN070159T1000	LDC4K Additional Coil Terminal Block	LDC4K	1	piece
1SBN083406R1000	BEA65-4 Connecting Link with Manual Motor Starter	BEA65-4	1	piece

Identifier	Description	Type	Qty	Unit Of Measure
1SBN010160R1001	CA4-01K Auxiliary Contact Block	CA4-01K	1	piece
1SBN010146R1022	CA4-22EK Auxiliary Contact Block	CA4-22EK	1	piece
1SBN010160R1010	CA4-10K Auxiliary Contact Block	CA4-10K	1	piece
1SBN010160T1001	CA4-01K-T Auxiliary Contact Block	CA4-01K-T	1	piece
1SBN010160T1010	CA4-10K-T Auxiliary Contact Block	CA4-10K-T	1	piece
1SBN010146R1031	CA4-31EK Auxiliary Contact Block	CA4-31EK	1	piece
1SBN010146R1040	CA4-40EK Auxiliary Contact Block	CA4-40EK	1	piece

Categories

Products > Low Voltage Products and Systems > Control Products > Contactors > Block Contactors > AF Contactors > AF52

